


## level



## DESCRIZIONE | DESCRIPTION

- Miscelatore termostatico incasso doccia (2 uscite) completo di:
  - piastra 150x200mm
  - attacchi 1/2"G
- Concealed thermostatic shower mixer (2 outlets) complete with:
  - wall plate 150x200mm
  - 1/2"G connections

## FINITURE | FINISHES

## LEQ 518..

- CR - Cromo | Chrome
- CR/M - Cromo con piastra acciaio inox | Chrome with stainless steel wall plate
- ST/M - Steel looking con piastra acciaio inox | Steel looking with stainless steel wall plate

## ARTICOLO | ARTICLE

## LEQ 518..

- con cartuccia deviatore (2 uscite + stop)
- with diverter cartridge (2 outlets + stop)

## RAPPORTO PROVA PORTATA | FLOW RATE REPORT

	Uscita outlet	Pressione / Pressure ( bar )									
		0,5	1	1.5	2	2.5	3	3.5	4	4.5	5
Portata / Flow rate ( l / min )	uscita destra - right outlet	6.48	9.66	12.07	14.08	15.9	17.5	19.06	20.47	21.79	22.98
	uscita sinistra - left outlet	6.31	9.47	11.75	13.78	15.94	17.68	19.16	20.41	21.83	23

## DOCUMENTI TECNICI | TECHNICAL DOCUMENTS

DIAGRAMMA  
PORTATA 1ISTRUZIONI  
INSTALLAZIONEESPLOSO  
RICAMBI  
LEQ 518